

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number
WO 2005/029623 A3(51) International Patent Classification:
H01M 8/02 (2006.01)[JP/JP]. OTANI, Keizo [JP/JP]. OOE, Shinji [JP/JP].
KANO, Makoto [JP/JP].(21) International Application Number:
PCT/JP2004/0 12231(74) Agents: MIYOSHI, Hidekazu et al.; Toranomon Koto-
hira Tower, 2-8, Toranomon 1-chome, Minato-ku, Tokyo
105-0001 (JP).

(22) International Filing Date: 19 August 2004 (19.08.2004)

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:
2003-330633 22 September 2003 (22.09.2003) JP
2004-162988 1 June 2004 (01.06.2004) JP(71) Applicant (for all designated States except US): NISSAN
MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kana-
gawa-ku, Yokohama-shi, Kanagawa 2210023 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CHIBA, Nobutaka

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: SEPARATOR FOR FUEL CELL, FUEL CELL STACK, METHOD FOR MANUFACTURING SEPARATOR FOR
FUEL CELL, AND FUEL CELL VEHICLE

(57) Abstract: A separator for a fuel cell comprises a corrugated or undulated gas flow path portion (4) formed on central portion (2) of a clad thin plate: and a flat portion (6) formed on an outer periphery of the central portion, wherein the clad thin portion is obtained by applying rolling work on a metal plate whose surface is covered with a precious metal layer at a draft of 5% to 15% to make clad, and a limit plate thickness residual rate indicating a boundary limit in which cracking of the precious metal layer in the clad thin plate and reduction of corrosion resistance due to exposure of the metal plate are negligible is obtained in advance, wherein regarding a sectional shape in a direction orthogonal to a flow path of the gas flow path portion (4), when a plate thickness of the thinnest portion of a rib shoulder portion is represented as t2 and a plate thickness of a peripheral portion of the separator is represented as t4, a relationship of $t2 > 14 \times \text{limit plate thickness residual rate}$ is satisfied.



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE,
SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:

16 February 2006